




# Powerware

## Power Distribution Unit (PDU)

Designed for use with the Powerware® FERRUPS® and 9170 Uninterruptible Power System

### Features

- Eaton's softwired Power Distribution Unit (PDU) allows you to expand the number of output receptacles for the FERRUPS and 9170 uninterruptible power systems (UPS)
- Powerware's PDUs plug directly into one of the output receptacles on the UPS and contain multiple output receptacles
- PDU units may be floor or wall mounted



### General Specifications


<b>Dimensions (HxWxD):</b>	3 x 7.8 x 10 inches
<b>Weight (approx.):</b>	8lbs.
<b>Safety Listings:</b>	UL 1778 and cUL (to CSA C22.2-107.1)

### INPUT/OUTPUT CONFIGURATIONS

#### PDU-0007 120/240V

Input: 6' line cord with L14-30P plug for UPS output voltage of 120/240 VAC (not 208 VAC).


Output: (2) 5-15R duplex receptacles with individual 15A circuit breakers for each duplex, and (4) 6-15R duplex receptacles with individual 15A circuit breakers for each duplex.



#### PDU-0008 120/240V

Input: 6' line cord with L14-30P plug for UPS output voltage of 120/240 VAC (not 208 VAC).


Output: (2) 5-15R duplex receptacles with individual 15A circuit breakers for each duplex, and (3) L6-30R simplex receptacles.



#### PDU-0009 120/240V

Input: 6' line cord with L14-30P plug for UPS output voltage of 120/240 VAC.

Output: 120V (6) 5-15R duplex receptacles with individual 15A circuit breakers for each duplex.




## INPUT/OUTPUT CONFIGURATIONS

### PDU-0010 208V or 240V

Input: 6' line cord with L6-30P plug for UPS output voltages of 208 or 240 VAC.


Output: (3) L6-20R simplex receptacles with individual 20A circuit breakers for each receptacle and (1) L6-30R simplex receptacle.



### PDU-0011 208V or 240V

Input: 6' line cord with L6-30P plug for UPS output voltages of 208 or 240 VAC.

Output: (4) L6-30R simplex receptacles.



### PDU-0012 120V

Input: 6' line cord with L5-30P plug for UPS output voltages of 120 VAC.

Output: (4) 5-15R duplex receptacles with individual 15A circuit breakers for each duplex.

Note: Designed for use with FERRUPS® and 9170 only — DO NOT plug directly into wall outlet.